

FHNG

Warm Air Heater

Stainless steel

Heating medium LPG/l 3 P
Heat output 18 – 100 kW
Air output 1,100 – 2,800
cbm/h
Fully automatic



FLEXIHEAT UK LTD
Flexible Heating & Dehumidification Solutions
01202 822221
www.flexiheatuk.com

Application:

- Exhibition halls
- Construction site heating
- Site drying
- De-icing
- Event rooms
- Marquees
- Airplane hangars
- Horticulture
- Grain drying
- Greenhouses
- Rooms for commercial use
- Industrial halls
- Storage rooms
- Agriculture
- Centres of logistics
- Production facilities
- Protection spaces
- Sports halls
- Stable heating
- Tennis halls
- Air domes
- Event tents
- Consumer markets
- Workshops

Handy and powerful:

The units of our FHNG series are technically finished, fair in consumption and variable in use inside rooms with ventilation.

Type FHNG 35 – 100

Fully automatic with electric ignition and ionisation flame control. Uncomplicated connection possibility to use a room thermostat via plug connection.

Included in delivery is a gas hose with pressure control (gas bottles 5.0 – 33.0 kilos). Heating capacity can be chosen variably within the stated range.

All units are optimally intended for frost-free maintenance of building sites and are often used for grain drying in agriculture.



Technical Data

Type	FHNG-	35	50	75	100	
Model		Fully automatic				
Nominal heat loading capacity	kW	18.0–35.0	25.0–50.0	35.0–70.0	50.0–100.0	
Air output	cbm/h	1,100	1,400	2,000	2,800	
Connected pressure	bar	2.5–10.0	2.5–10.0	2.5–10.0	2.5–10.0	
Connection value	kg/h	1.41–2.73	1.95–3.91	2.73–5.47	3.91–7.81	
Electric connection	V/Hz	230/50	230/50	230/50	230/50	
Current consumption	A	0.48	0.48	0.60	0.92	
Length	mm	500	650	800	1,000	
Width	mm	320	320	370	370	
Height	mm	460	460	520	520	
Weight	kg	14	16	21	26	
Product ID number		CE-0085 AQ 0232				
Control		Fully automatic with electrical ignition and possibilities to connect a room thermostat				

Subject to changes of dimensions and technical data (Version: 2013-06)