







Powerful curtain of warm air to minimise energy losses across the door



Vertical Gas Air Curtains - FACV series is specially designed to protect the building against uncontrolled external airflow through the doors. It helps to save energy which is used for keeping a desired temperature in the building. This series is made for vertical installation only.



Applications



Vertical Air Curtain

FACV gas air curtain can be used in conjunction with an ambient air curtain if the door is higher than 2 meters.

The ambient air curtain FAC45V2.0 is specially designed to protect the upper part of the door by recirculating the air from the building. The air curtain FAC45V2.0 works in ventilation only (no heating). When used in this vertical configuration of one gas fired vertical air curtain and one ambient air vertical curtain, the maximum height of 4 mtrs is covered and the maximum width of the door that they can be used on is 4 metres




- TAC45V Gas air curtain
- 2 FAC45V2.0- Ambientair curtain

→ Ambient air→ Warm air

Performances

Models	FAC 45 V	
Power (kW)	44	
Useful power (kW)	40.5	
Efficiency (%)	> 91	
Air flow (m3/h)	10 500	
Door width (m) *	2-4	





FACV

Prices

Models		FAC 45 V
Gas air curtain		FAC45V
Ambient air curtain		FAC45V2.0
	Natural gas kit 20 or 25 mBar	KGN20
nection	Natural gas kit 300 mBar	2 KDGN55
Gas connection	Propane gas kit 1,5 Bar	3 KDP55
	Flexible gas connection 3/4"	FLEXIND3/4
Fix.	Wall-mounting brackets	5 KYACV
ation	Switch disconnector	BSAT4P
Regulation	Thermostat + remote reset	TFP1- ET85P

