



FLEXIHEAT UK LTD
www.flexiheatuk.com
01202 822221

For heating and cooling

100%

FOSSIL-FREE
ELECTRIC
MOBILE
AUTOMATIC



Mobile air-to-air heat pumps
MWK40, MW40 and MW80

Mobile air-to-air heat pumps for heating and cooling

Environmentally friendly heating and cooling for all requirements



Environmentally friendly



Economical



Fossil-free



Mobile



Compact

The transformation in heat supply from fossil energy sources to regenerative concepts faces challenges, specifically regarding temporary solutions, as the resulting complexity often cannot be combined with the necessary flexibility.

With unstable price developments of fossil fuels and increasing CO₂ taxation, heat pumps offer an uncomplicated as well as sustain-

able and yet cost-effective heating solution. Depending on the version, our durable and easily transportable air-to-air heat pumps provide heating, as well as heating and cooling, completely without fossil fuels. Heating oil and gas are no longer required – an electricity connection is all that is needed.

Our **MWK40** allows year-round temperature control with just one unit

including mobile heating down to -10°C and cooling up to +40°C.

Our **MWK40** and **MW80** are designed for facing extreme temperature ranges down to -20°C but without the cooling function. Thanks to the air-to-air functionality, costly room installations are usually completely unnecessary. Any further installations of boilers or cooling units, radiators, and their pipe distributions with

Also in summer, you can keep a cool head at all times:

Our mobile heating/cooling combination **MWK40** handles outside temperatures up to +40°C and cools your objects without any problems.



MWK40/
MW40



Areas of application

- (Large) construction sites
- Warehouses and production halls
- (Large) events
- (Festival) tents
- Agriculture
- Commercial, municipal, and private requirements such as temporary heating, replacement heating in case of failure of stationary heating systems or temperature control/air conditioning.



Award

The Plus X Award is **one of the world's biggest innovation prizes for technology, sports and lifestyle**, with independent expert jurors from over 80 industries and more than 700 participating international brands.

The expert jury, consisting of editors, designers and industry experts, awards various quality seals to products that stand out for their genuine quality and innovative edge.

Our MWK40 earned the quality seal in five of a total of seven categories.





pumps, fittings and control technology become unnecessary.

Outside-installed heat pumps temper the room air directly to the desired target temperature via a circulating airflow. Mobile air-to-air heat pumps have been designed for quick installation and commissioning. The temperature control solution is ready for operation within a very short time.

No tank systems, no fuel storage, and much lower maintenance – thanks to the air-to-air operation, you also don't have to worry about water chillers compared to air-to-water heat pumps. Inlet and outlet nozzles are recessed in the housing. There are no protruding components. Safe loading is ensured by openings for forklift trucks. The high external pressure allows long hose connections.

Air-to-air heat pumps can also be used for stationary applications with a permanently installed air duct system.

With the help of a web application and a mobile internet connection, all devices can be managed, monitored and billed.

Characteristics

- Scroll-Compressor
- Refrigerant R410A
- Axial blowers with sickle blades
- Radial fan
- Via frequency inverter speed-controlled blowers for the optimum air volume
- 200 Pa external delivery pressure
- Purely electrical operation with 400 V/50 Hz/32 A
- Pressure transmitter for low and high pressure side
- Dimensions: 2,400 x 1,200 x 2,200 mm (L x W x H)
- Heat capacity 42.9 kW
- Cooling capacity 33.5 kW
- Application ambient temperature -10 °C to +40 °C
- Maximum efficiency COP 2.88/EER 3.3
- Volume 8,000 m³/h



Info

Even under extreme conditions of up to -10°C or -20°C outside temperature, our mobile heat pumps provides enough heat for your properties, completely fossil-free – for 100 percent comfortable indoor climate.

Remote control via web browser.

Special colors available on request.

MW80



Technical Data

Power range 14 to 100 kW

| | | MWK40 | MW40 | MW80 |
|--|-------------------|---------------------|--------------------------|--------------------------|
| Product code | | 300686 | 301531 | 301532 |
| Function | | Heating and cooling | Heating | Heating |
| Application ambient temperature | °C | -10 to +40 | -20 to +25 | -20 to +25 |
| Heat capacity (A7/L35) | kW | 42.9 | 42.4 | 100.4 |
| Cooling capacity (A30/L12) | kW | 33.5 | - | - |
| COP _h (A-7/L35) without utilizable medium | | 2.24 | 2.30 | 2.34 |
| COP _h (A2/L35) without utilizable medium | | 2.88 | 2.76 | 2.77 |
| COP _h (A7/L35) without utilizable medium | | 3.31 | 3.07 | 3.06 |
| SCOP _h without utilizable medium | | 2.88 | 2.72 | 2.73 |
| COP _h (A-7/L35) with utilizable medium | | 1.95 | 1.96 | 2.04 |
| COP _h (A2/L35) with utilizable medium | | 2.50 | 2.42 | 2.46 |
| COP _h (A7/L35) with utilizable medium | | 2.88 | 2.69 | 2.71 |
| SCOP _h with utilizable medium | | 2.45 | 2.34 | 2.38 |
| Volume | m ³ /h | 8,000 | 8,000 | 16,000 |
| External pressure | Pa | 200 | 200 | 250 |
| Electrical connection | V/Ph/Hz | 400/3/50 | 400/3/50 | 400/3/50 |
| Connector plug | | 32A CEE | 32A CEE | 63A CEE |
| Max. nominal current | A | 31 | 31 | 62 |
| Connection Ø air current | mm | 525 | 525 | 525 |
| Length | mm | 2,400 | 2,400 | 3,000 |
| Width | mm | 1,200 | 1,200 | 2,300 |
| Height | mm | 2,200 | 2,200 | 2,350 |
| Weight | kg | 1,000 | 1,100 | 2,700 |
| Sound pressure level | dB(A) | 66 | 66 | 68 |
| Refrigerant | | R410A | R454C | R454C |
| Compressor | | Scroll | reciprocating compressor | reciprocating compressor |
| Condensate quantity max. | liter/h | 10 | 10 | 20 |
| Nozzle condensate drain (external) | Inch | 1 1/4 | 1 1/4 | 1 1/4 |

A – ambient temperature (°C) | L – room air temperature (°C) | COP – coefficient of performance (h – heating/c – cooling) | SCOP – annual performance

Accessories

MWK40, MW40, MW80

| | | | | |
|---|-------|----------|--------------|--------|
| Hot air hose with fastening belt and carrying bag | 7.6 m | Ø 305 mm | Product code | 005597 |
|---|-------|----------|--------------|--------|

Options for the MWK40, MW40 and MW80

Remote query (extra charge)

Our **heat pumps** are equipped with a router by default. This provides you with a **Wi-Fi connection** and control on-site with a range of approx. 5 meters.

Optionally, remote access to operating parameters can be booked throughout Europe. In addition to remote queries of the devices, operating data and the device status can also be viewed.

On request, we can add further options to the access, such as the retrieval of historical data.



Remote maintenance (extra charge)

Upon request, we can offer **remote maintenance** of your devices.

We not only take care of the **maintenance** of your heat pumps but also provide you with regular **diagnostic reports** of the operating status.

In addition, we take care of **necessary software updates**.

Our availability on working days between 8 am and 4 pm is guaranteed.



Do you have any other requirements which are not listed here?

Please do not hesitate to contact us!

We have both the engineering know-how and the mechanical equipment to implement your individual requirements with our usual Kroll Energy quality.

Together, we can master any air-conditioning challenge and reach your desired temperatures environmentally- and budget-friendly.



Application examples





FLEXIHEAT UK LTD

www.flexiheatuk.com

01202 822221